NSN 5935-00-257-6860

Plug-in Electronic Components Socket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-257-6860 **Body Material:** Ceramic **Body Style:** Top mount w/metal saddle and shield base **Fabrication Method:** Molded **Body Surface Treatment:** Glazed **Overall Length:** 1.125 inches **Tempurature Rating:** 200.0 degrees celsius **Overall Height:** 1.188 inches **Overall Width:** Between 0.795 inches and 0.805 inches **Mounting Hole Diameter:** Between 0.120 inches and 0.130 inches **Body Mounting Hole Accommodation Diameter:** 0.620 inches **Distance Between Mounting Facility Centers:** Between 0.870 inches and 0.880 inches **Mounting Hole Style:** Round, w/two mounting holes **Contact Resistance In Ohms:** 0.015 **Specific Equipment Accommodated:** Electron tube **Contact Maximum Current Rating In Amps:** 1.0 **Contact Material:** Beryllium copper **Contact Surface Treatment:** Gold and copper **Accommodated Contact Quantity: Component Shield Mounting Method:** Bead **Polarization Type:** Slot Saddle Material:

Brass

NSN 5935-00-257-6860 Plug-in Electronic Components Socket - Page 2 of 2



Saddle Surface Treatment:	
Tin	
Base Shield Material:	
Brass	
Projection Length Below Mounting Surface:	
0.547 inches	
Mounting Method:	
Saddle	
Mounting Type For Which Designed:	
Chassis	
Features Provided:	
Center shield	
Contact Position Arrangement Style:	
Miniature	
Contact Maximum Voltage In Volts And Current Type:	
500.0 ac and 500.0 dc	
Terminal Type And Quantity:	
7 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
- -	
Demilitarization:	
No	
Fiig:	
A02300	