NSN 5935-00-257-7312

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-257-7312
Body Style:
Straight shape, external coupling
Overall Length:
1.156 inches
Bushing Diameter:
0.348 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.531 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.531 inches
Distance From Mounting Shoulder To Front Face:
0.308 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Bnc single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Frequency Rating:

10000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic polystyrene single mating end

Terminal Type:

Solder well single mating end single contact grouping

NSN 5935-00-257-7312

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Copper alloy
Shell Surface Treatment:
Silver
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact and shell surfaces silver
Precious Material And Weight:
0.101 silver grains, troy
Precious Material:
Silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0