Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-257-7317

| Thread Class:  |
|--|
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Body Style:  |
| Thru-hole mount  |
| Overall Length:  |
| 0.812 inches   |
| Bushing Diameter:  |
| 0.625 inches   |
| Overall Diameter:  |
| 0.875 inches   |
| Distance From Mounting Shoulder To Rear Face:  |
| 0.750 inches   |
| Threaded Device Type:  |
| Mounting bushing   |
| Mating End Quantity:   |
| 1  |
| Contact Position Arrangement Style:  |
| 2 single mating end  |
| Contact Removability:  |
| Nonremovable single mating end single contact grouping   |
| Connector Locking Method:  |
| Friction   |
| Thready Qty Per Inch (tpi):  |
| 24   |
| Thread Size:   |
| 0.625 inches   |
| Terminal Location:   |
| Back single mating end single contact grouping   |
| Contact Material:  |
| Copper alloy single mating end single contact grouping   |
| Contact Surface Treatment:   |
| Silver single mating end single contact grouping   |
| Insert Material:   |
| Plastic single mating end  |
| Contact Surface Treatment Specification:   |
| Qq-s-365 federal specification single treatment response single mating end single contact grouping |
| Terminal Type:   |
| Solder well single mating end single contact grouping  |
| Included Contact Quantity:   |
| 2 single mating end single contact grouping  |
|  |



Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.010 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0