

View Online at <https://aerobasegroup.com/nsn/5935-00-257-7458>

Thread Class:

2a

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Gk-1 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

40.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

125.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

125.0 single mating end single contact grouping

Thread Length:

0.500 inches

Thread Size:

0.875 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic single mating end

Terminal Type:

Threaded stud single mating end single contact grouping

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round pin single mating end single contact grouping

Test Data Document:

73338-9000-s6202, type h-16b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unef

Reference Number Differentiating Characteristics:

As differentiated by reply to contact style reqmt

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0