## NSN 5935-00-257-8561

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-257-8561 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, latching **Overall Length:** 0.532 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Mh-5 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Contact Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material: Plastic Insert Material Specification:** 

Mil-p-4339 military specification single material response single mating end

**Included Contact Quantity:** 

5 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round

## NSN 5935-00-257-8561

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Type:** Round socket single mating end single contact grouping Color: Natural **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.005 gold grains, troy and 0.005 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig:

A039b0

Mil-p-4339 spec.

Mil-std (military Standard):