Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-257-8561

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, latching |
| Overall Length: |
| 0.532 inches |
| Threaded Device Type: |
| Mounting bushing |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Mh-5 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 5.0 single mating end single contact grouping |
| Polarization Method: |
| Contact |
| Thready Qty Per Inch (tpi): |
| 20 |
| Thread Size: |
| 0.500 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Insert Material: |
| Plastic single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Plastic |
| Insert Material Specification: |
| Mil-p-4339 military specification single material response single mating end |
| Included Contact Quantity: |
| 5 single mating end single contact grouping |
| Bushing Accommodation Hole Shape: |
| Round |
| |



Included Contact Type: Round socket single mating end single contact grouping Color: Natural **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.005 gold grains, troy and 0.005 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-p-4339 spec.