Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-257-8683

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, latching
Overall Width:
0.625 inches
Diameter:
0.563 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
Contact Position Arrangement Style:
Nk-b9 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
660.0 single mating end single contact grouping
Polarization Method:
Contact
Thread Length: 0.250 inches
Thready Qty Per Inch (tpi):
20
Thread Size:
0.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type: Solder well single mating and single contact grouping
Solder well single mating end single contact grouping
Included Contact Quantity:
9 single mating end single contact grouping

NSN 5935-00-257-8683

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.009 gold grains, troy and 0.009 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0