NSN 5935-00-257-9265

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-257-9265 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.750 inches **Overall Height:** 1.375 inches **Overall Width:** 1.375 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.038 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.038 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Sk-m10 single mating end **Contact Removability:** Removable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 30.0 single mating end 1st contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: Potting **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Potting type Thready Qty Per Inch (tpi): Thread Size:

1.312 inches

NSN 5935-00-257-9265

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Plastic polytetrafluoroethylene single mating end
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
8 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0