

View Online at <https://aerobasegroup.com/nsn/5935-00-257-9404>

Thread Class:

2a

Thread Direction:

Right-hand

Body Length:

Between 1.390 inches and 1.609 inches

Overall Diameter:

Between 2.219 inches and 2.312 inches

Environmental Protection:

Watertight

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

28-2 single mating end

Contact Maximum Current Rating In Amps:

41.0 single mating end 1st contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

1250.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

18

Thread Size:

1.750 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Insert Material:

Plastic diallyl phthalate mineral filled single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Copper alloy

Shell Surface Treatment:

Anodize

Included Contact Quantity:

2 single mating end 1st contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round pin single mating end all contact groupings

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0