## NSN 5935-00-257-9740

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-00-257-9740 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.222 inches **Overall Height:** Between 1.335 inches and 1.351 inches **Overall Width:** Between 1.335 inches and 1.351 inches **Environmental Protection:** Moisture resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.126 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** Between 1.057 inches and 1.067 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.057 inches and 1.067 inches **Distance From Mounting Shoulder To Front Face:** Between 0.765 inches and 0.775 inches **Threaded Device Type:** Back shell **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 16-55 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thread Length: 0.335 inches

28

Thready Qty Per Inch (tpi):

## NSN 5935-00-257-9740

Electrical Receptacle Connector - Page 2 of 3



Thread Size:
1.125 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204, type, cl 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Shell Material Specification:
Qq-a-367, comp 6061, t6 federal specification single material response
Included Contact Quantity:
55 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.055 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Un
Specification Data:
81349-mil-c-81511/51 government specification
Shelf Life:
N/a
Unit Of Measure:

Fiig:

No

Demilitarization:

## NSN 5935-00-257-9740

Electrical Receptacle Connector - Page 3 of 3



Mil-std (military Standard):

Mil-g-45204 spec.