## NSN 5935-00-258-0196

Solder well single mating end single contact grouping

Electrical Receptacle Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-258-0196



**Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.406 inches **Overall Diameter:** 0.812 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Tnc single mating end **Contact Removability:** Removable single mating end single contact grouping **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Length: 0.719 inches Thready Qty Per Inch (tpi): 16 Thread Size: 0.750 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Plastic polyamide single mating end **Contact Surface Treatment Specification:** Qq-s-365 federal specification single treatment response single mating end single contact grouping **Terminal Type:** 

## NSN 5935-00-258-0196

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Copper alloy
Shell Surface Treatment:
Silver
Shell Surface Treatment Specification:
Qq-s-365 federal specification single treatment response
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact and body surfaces silver
Precious Material And Weight:
0.105 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
No Fiig: