Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-258-0208

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Round flange mount, external coupling
Overall Length:
3.250 inches
Bushing Diameter:
2.437 inches
Overall Diameter:
4.750 inches
Environmental Protection:
Weather resistant
Unthreaded Mounting Hole Diameter:
0.216 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
B4s single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
30.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
300.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
4
Thread Size:
2.500 inches



**Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Screw single mating end single contact grouping Shell Material: Aluminum alloy **Included Contact Quantity:** 4 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0