NSN 5935-00-258-0213



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-258-0213 **Thread Class:** 2b and 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 0.875 inches **Overall Height:** 0.781 inches **Overall Width:** 0.781 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.560 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.562 inches **Threaded Device Type:** Coupling facility and mounting hole **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Internally threaded coupling ring Thready Qty Per Inch (tpi): 24 and 36

Thread Size:

0.625 inches and 0.112 inches

Insert Material:

Plastic single mating end

NSN 5935-00-258-0213

Electrical Receptacle Connector - Page 2 of 2



| Terminal Type: |
|--|
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Included Contact Quantity: |
| 1 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Thread Series Designator: |
| Unef and uns |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A039b0