Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-258-0351



# Thread Class:

2a

**Thread Direction:** 

Right-hand

## Body Style:

Straight shape, external coupling

#### **Overall Length:**

Between 2.250 inches and 2.343 inches

#### **Overall Diameter:**

2.344 inches

### **Environmental Protection:**

Watertight

**Threaded Device Type:** 

Coupling facility

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

32-17 single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

135.0 single mating end single contact grouping

#### Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end single contact grouping

#### Contact Maximum Dc Voltage Rating In Volts:

1250.0 single mating end single contact grouping

#### **Polarization Method:**

Key, multiple key groove

#### **Insert Position In Deg:**

0.0

#### Shell Type:

Potting

## **Connector Locking Method:**

Externally threaded shell

# Connector Cable Strain Relief Method:

Potting type

# Thready Qty Per Inch (tpi):

18

Thread Size:

2.000 inches

**Terminal Location:** 

Back single mating end single contact grouping

# **NSN 5935-00-258-0351** Electrical Plug Connector - Page 2 of 2



Contact Material:	
Copper alloy single mating end	single contact grouping
Contact Surface Treatment:	
Gold single mating end single of	contact grouping and copper single mating end single contact grouping
Insert Material:	
Plastic diallyl phthalate mineral	filled single mating end
Contact Surface Treatment S	pecification:
Mil-g-45204, type 1, class 2 mi	litary specification 1st treatment response single mating end single contact grouping and mil-c-14550 class 4
military specification 2nd treatm	nent response single mating end single contact grouping
Terminal Type:	
Solder well single mating end s	ingle contact grouping
Shell Material:	
Aluminum alloy	
Shell Surface Treatment:	
Anodize	
Shell Surface Treatment Spe	cification:
Mil-a-8625 military specification	single treatment response
Insert Material Specification:	
Mil-c-5015 military specification	n single material response single mating end
Included Contact Quantity:	
4 single mating end single cont	act grouping
Included Contact Type:	
Round pin single mating end si	ngle contact grouping
Precious Material And Locati	on:
Contact surfaces gold	
Precious Material And Weigh	t:
0.020 gold grains, troy	
Precious Material:	
Gold	
Thread Series Designator:	
Uns	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-g-45204 spec.	