Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-258-0448

| Thread Direction:                                   |
|---|
| Right-hand  |
| Overall Length:                                     |
| 1.625 inches  |
| Overall Diameter:                                   |
| 2.500 inches  |
| Environmental Protection:                           |
| Pressure proof and corrosion resistant              |
| Threaded Device Type:                               |
| Back shell  |
| Mating End Quantity:                                |
| 1   |
| Contact Maximum Current Rating In Amps:             |
| 135.0 single mating end all contact groupings       |
| Contact Maximum Ac Voltage Rating In Volts:         |
| 900.0 single mating end all contact groupings       |
| Contact Maximum Dc Voltage Rating In Volts:         |
| 1250.0 single mating end all contact groupings      |
| Connector Locking Method:                           |
| Externally threaded shell                           |
| Thready Qty Per Inch (tpi):                         |
| 18  |
| Thread Size:  |
| 2.000 inches  |
| Insert Material:                                    |
| Plastic single mating end                           |
| Shell Material:                                     |
| Aluminum alloy                                      |
| Included Contact Quantity:                          |
| 4 single mating end all contact groupings           |
| Included Contact Type:                              |
| Round pin single mating end all contact groupings   |
| Special Features:                                   |
| Dim. Excl protruding contacts; polarized; panel mtg |
| Thread Series Designator:                           |
| Uns   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:                                    |
|   |
| <br>Demilitarization:                               |
| No  |
|   |
|   |

## NSN 5935-00-258-0448

Electrical Receptacle Connector - Page 2 of 2

**Fiig:** A039b0

