

View Online at <https://aerobasegroup.com/nsn/5935-00-258-0562>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Round flange mount, external coupling

Overall Length:

1.562 inches

Mounting Hole Circle Radius:

1.250 inches

Overall Diameter:

3.188 inches

Environmental Protection:

Watertight

Unthreaded Mounting Hole Diameter:

0.125 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

22-20 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

20.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

150.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

200.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.344 inches

Thready Qty Per Inch (tpi):

10

Thread Size:

1.812 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Qq-s-365 federal specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Chromate

Included Contact Quantity:

9 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.009 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0