Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-258-0566

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Body Style:	
Round flange mount, external coupling	
Overall Length:	
1.343 inches	
Bushing Diameter:	
2.312 inches	
Overall Diameter:	
4.250 inches	
Environmental Protection:	
Watertight	
Unthreaded Mounting Hole Diameter:	
0.265 inches	
Distance From Mounting Shoulder To Rear Face:	
0.375 inches	
Threaded Device Type:	
Coupling facility	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
22-48 single mating end	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
10.0 single mating end single contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
150.0 single mating end single contact grouping	
Contact Maximum Dc Voltage Rating In Volts:	
200.0 single mating end single contact grouping	
Polarization Method:	
Mating end	
Shell Type:	
Solid	
Thready Qty Per Inch (tpi):	
10	
Thread Size:	
2.750 inches	
Terminal Location:	
Back single mating end single contact grouping	



**Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** Nickel **Included Contact Quantity:** 48 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surface silver **Precious Material And Weight:** 0.048 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Uns Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0