

View Online at <https://aerobasegroup.com/nsn/5935-00-258-0700>

**Thread Class:**

2a

**Thread Pitch Diameters:**

+0.243 to 0.249 inches

**Thread Direction:**

Right-hand

**Electrical Insulation Feature:**

Insulated completely

**Identification Code Color:**

Red

**Body Style:**

Threaded bushing mounted

**Overall Length:**

1.131 inches

**Mounting Bushing Length:**

0.428 inches

**Body Length:**

0.969 inches

**Overall Diameter:**

0.281 inches

**Bushing Accommodation Hole Shape:**

Round

**Maximum Voltage Rating In Volts:**

5000.0 dc

**Accommodated Finger Type:**

Test prod stepped single finger

**Finger Accommodation Diameter:**

0.080 inches single finger

**Finger Accommodation Length:**

0.678 inches single finger

**Bushing Thru-hole Accommodation Diameter:**

0.281 inches

**Capacitance In Picofarads:**

6.0

**Current Rating In Amps:**

5.0

**Mounting Facility Type And Quantity:**

1 threaded stud

**Thread Size:**

0.250 inches

**Terminal Type:**

Turret

**Material:**

Plastic, diallyl phthalate cap

**Material:**

Plastic diallyl phthalate cap

**Surface Treatment:**

Copper and gold terminal

**Surface Treatment:**

Copper terminal and gold terminal

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03400