NSN 5935-00-258-0700

Tip Jack - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-258-0700



Thread Class: 2a **Thread Pitch Diameters:** +0.243 to 0.249 inches Thread Direction: **Right-hand Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Red **Body Style:** Threaded bushing mounted **Overall Length:** 1.131 inches Mounting Bushing Length: 0.428 inches **Body Length:** 0.969 inches

Overall Diameter:

0.281 inches

Bushing Accommodation Hole Shape:

Round

Maximum Voltage Rating In Volts:

5000.0 dc

Accommodated Finger Type:

Test prod stepped single finger

Finger Accommodation Diameter:

0.080 inches single finger

Finger Accommodation Length:

0.678 inches single finger

Bushing Thru-hole Accommodation Diameter:

0.281 inches

Capacitance In Picofarads:

6.0

Current Rating In Amps:

5.0

Mounting Facility Type And Quantity:

1 threaded stud

Thread Size:

0.250 inches

Terminal Type:

Turret

NSN 5935-00-258-0700

Tip Jack - Page 2 of 2

Material: Plastic, diallyl phthalate cap Material: Plastic diallyl phthalate cap Surface Treatment: Copper and gold terminal Surface Treatment: Copper terminal and gold terminal Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A03400

