NSN 5935-00-258-0704

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-258-0704

Thread Classe	
Thread Class:	
2a Thread Bitch Diameters	
Thread Pitch Diameters:	
+0.243 to 0.249 inches	
Thread Direction:	
Right-hand	
Electrical Insulation Feature:	
Insulated completely	
Identification Code Color:	
Orange	
Body Style:	
Threaded bushing mounted	
Overall Length:	
1.131 inches	
Mounting Bushing Length:	
0.428 inches	
Body Length:	
0.969 inches	
Overall Diameter:	
0.281 inches	
Bushing Accommodation Hole Shape:	
Round	
Maximum Voltage Rating In Volts:	
5000.0 dc	
Accommodated Finger Type:	
Test prod stepped single finger	
Finger Accommodation Diameter:	
0.080 inches single finger	
Finger Accommodation Length:	
0.678 inches single finger	
Bushing Thru-hole Accommodation Diameter:	
0.281 inches	
Capacitance In Picofarads:	
6.0	
Current Rating In Amps:	
5.0	
Mounting Facility Type And Quantity:	
1 threaded stud	
Thread Size:	
0.250 inches	
Terminal Type:	
Turret	

NSN 5935-00-258-0704

Tip Jack - Page 2 of 2

Material: Plastic, diallyl phthalate cap Material: Plastic diallyl phthalate cap Surface Treatment: Copper and gold terminal Surface Treatment: Copper terminal and gold terminal Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A03400

