Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-258-0718

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape threaded
Overall Length:
Between 1.390 inches and 1.609 inches
Overall Diameter:
1.750 inches
Environmental Protection:
Watertight
Distance From Mounting Shoulder To Front Face:
Between 1.094 inches and 1.390 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
28-16 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
80.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
18 and 18
Thread Size:
1.750 inches and 1.750 inches
Terminal Location:
Back single mating end single contact grouping



	ontact Material:
	opper alloy single mating end single contact grouping ontact Surface Treatment:
	lver single mating end single contact grouping sert Material:
	astic single mating end
	ontact Surface Treatment Specification:
	q-s-365 federal specification single treatment response single mating end single contact grouping
	erminal Type:
	older well single mating end single contact grouping
	nell Material:
-	uminum alloy
	nell Surface Treatment:
An	nodize
Ine	cluded Contact Quantity:
20) single mating end single contact grouping
Βι	ushing Accommodation Hole Shape:
Rc	bund
Ind	cluded Contact Type:
Rc	ound pin single mating end single contact grouping
Pr	recious Material And Location:
Сс	ontact surfaces silver
Pr	ecious Material And Weight:
0.0	020 silver grains, troy
Pr	recious Material:
Sil	lver
Th	nread Series Designator:
	ns and uns
Sh	nelf Life:
N/	
Ur	nit Of Measure:
	emilitarization:
Nc	
Fii	ig:
AC	03960