

View Online at <https://aerobasegroup.com/nsn/5935-00-258-1094>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Overall Length:**

1.875 inches

**Overall Height:**

1.250 inches

**Overall Width:**

1.125 inches

**Unthreaded Mounting Hole Diameter:**

0.156 inches

**Distance Between Mounting Facility Centers:**

1.500 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

22.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.125 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Silver single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Anodize

**Special Features:**

Enviromental protection: incombustible; contact qty: 10; contact type: round pin

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.010 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0