## NSN 5935-00-258-1095

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-258-1095 **Thread Class:** 2a **Thread Direction:** Right-hand **Overall Length:** 1.188 inches **Overall Height:** 0.969 inches **Overall Width:** 1.188 inches **Environmental Protection:** Pressure proof **Unthreaded Mounting Hole Diameter:** 0.128 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 20.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 50.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 70.0 single mating end single contact grouping **Connector Locking Method:** Externally threaded shell **Thread Size:** 0.875 inches **Insert Material:** Rubber single mating end **Shell Material:** Aluminum alloy **Shell Surface Treatment:** 

Anodize **Included Contact Quantity:** 

4 single mating end single contact grouping

## NSN 5935-00-258-1095

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Ty	pe:
----------	---------	----	-----

Round socket single mating end single contact grouping

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0