

View Online at <https://aerobasegroup.com/nsn/5935-00-258-1734>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape w/cable clamp

**Overall Length:**

1.812 inches

**Bushing Diameter:**

0.687 inches

**Overall Height:**

1.000 inches

**Overall Width:**

1.000 inches

**Environmental Protection:**

Watertight

**Unthreaded Mounting Hole Diameter:**

0.125 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.719 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.719 inches

**Cable Entrance Diameter:**

0.195 inches

**Distance From Mounting Shoulder To Front Face:**

0.654 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Nonstd single mating end

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Connector Cable Strain Relief Method:**

Compression nut

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

52.0 single mating end single contact grouping

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.625 inches

**Terminal Location:**

Back single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Shell surface silver

**Precious Material And Weight:**

0.100 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0