NSN 5935-00-258-1740

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-258-1740 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.094 inches **Overall Height:** 1.000 inches **Overall Width:** 1.000 inches **Environmental Protection:** Corrosion resistant and watertight and dustproof **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.718 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.718 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Rf single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.625 inches **Terminal Location:** Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-00-258-1740

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:
Wire wrap single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Gold
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Special Features:
Furnished items - mounting plate
Precious Material And Location:
Contact and shell surfaces gold
Precious Material And Weight:
0.105 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: