NSN 5935-00-258-2703

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-258-2703

| Thread Class: |
|---|
| 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape |
| Overall Length: |
| 2.620 inches |
| Overall Width: |
| 0.440 inches |
| Distance Between Mounting Facility Centers: |
| 2.312 inches |
| Threaded Device Type: |
| Mounting stud |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Ak-d39 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Polarization Method: |
| Guide pin/socket |
| Thread Size: |
| 0.112 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and silver single mating end single contact grouping and gold single mating end single |
| contact grouping |
| Insert Material: |
| Plastic melamine single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Insert Material Specification: |
| Mil-m-14, type mme military specification single material response single mating end |
| Included Contact Quantity: |
| 41 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |

Precious Material And Weight:

0.041 gold grains, troy and 0.041 silver grains, troy

Contact surface gold and contact surface silver

NSN 5935-00-258-2703

Electrical Receptacle Connector - Page 2 of 2



| Gold and silver |
|--------------------------|
| Thread Series Designator |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Mil-std (military Standard):

Mil-m-14 spec.

Precious Material: