

View Online at <https://aerobasegroup.com/nsn/5935-00-258-2715>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.542 inches

Overall Height:

Between 1.980 inches and 2.020 inches

Overall Width:

Between 1.980 inches and 2.020 inches

Environmental Protection:

Moisture proof and vibration resistant and watertight

Unthreaded Mounting Hole Diameter:

Between 0.175 inches and 0.181 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.557 inches and 1.567 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.557 inches and 1.567 inches

Distance From Mounting Shoulder To Front Face:

Between 0.812 inches and 0.828 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

28-12 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

18 and 18

Thread Size:

1.625 inches and 1.750 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Rubber single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Included Contact Quantity:

26 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surface silver

Precious Material And Weight:

0.026 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unef and uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0