NSN 5935-00-258-2848

Electrical Plug Connector - Page 1 of 2





Thread Class: 2a and 2b **Thread Direction:** Right-hand and right-hand **Overall Length:** 2.062 inches **Overall Diameter:** 1.344 inches **Threaded Device Type:** Back shell and coupling facility Mating End Quantity: 1 **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 20.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 150.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 200.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 110.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut Thready Qty Per Inch (tpi): 20 and 18 **Thread Size:** 1.000 inches and 1.125 inches Shell Material: Aluminum alloy **Shell Surface Treatment:** Anodize **Included Contact Quantity:** 5 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Thread Series Designator:** Unef and unef

NSN 5935-00-258-2848

Electrical Plug Connector - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

