NSN 5935-00-258-2946

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-258-2946 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.328 inches **Overall Height:** 3.937 inches **Overall Width:** 3.375 inches **Unthreaded Mounting Hole Diameter:** 0.144 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 3.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.359 inches **Distance From Mounting Shoulder To Front Face:** 0.078 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 78 all mating ends **Contact Removability:** Nonremovable all mating ends single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 all mating ends single contact grouping **Polarization Method:** 2 polarization posts Shell Type: Solid **Connector Locking Method:** Jackscrew Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches

Terminal Location:

Back all mating ends single contact grouping

NSN 5935-00-258-2946

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy all mating ends single contact grouping
Contact Surface Treatment:
Silver all mating ends single contact grouping
Insert Material:
Plastic diallyl phthalate all mating ends
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response all mating ends single contact grouping
Terminal Type:
Solder well all mating ends single contact grouping
Contact Material Specification:
Qq-c-533 federal specification single material response all mating ends single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Shell Material Specification:
Qq-a-591/a380 federal specification single material response
Insert Material Specification:
Mil-m-14 military specification single material response all mating ends
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.156 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard): Mil-m-14 spec.