

View Online at <https://aerobasegroup.com/nsn/5935-00-258-2959>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, latching

Overall Length:

0.532 inches

Overall Width:

0.719 inches

Diameter:

0.656 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Contact

Connector Locking Method:

Latching ring

Thready Qty Per Inch (tpi):

20

Thread Size:

0.500 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic melamine single mating end

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type mme military specification single material response single mating end

Included Contact Quantity:

9 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.009 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.