

NSN 5935-00-258-2959 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-258-2959 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, latching **Overall Length:** 0.532 inches **Overall Width:** 0.719 inches Diameter: 0.656 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Contact **Connector Locking Method:** Latching ring Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.500 inches **Terminal Location:** Back single mating end single contact grouping

back single mating end single contact grot

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic melamine single mating end

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type mme military specification single material response single mating end

Included Contact Quantity:

9 single mating end single contact grouping

NSN 5935-00-258-2959

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.009 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):