

View Online at <https://aerobasegroup.com/nsn/5935-00-258-3010>

Thread Class:

2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape threaded

Overall Length:

Between 0.922 inches and 0.953 inches

Overall Diameter:

Between 1.297 inches and 1.328 inches

Environmental Protection:

Corrosion resistant and salt water resistant

Distance From Mounting Shoulder To Front Face:

Between 0.464 inches and 0.474 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

"18-8, 22-404" single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

4.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

24 and 24

Thread Size:

1.125 inches and 1.125 inches

Terminal Location:

Back single mating end single contact grouping

Terminal Type:

Turret single mating end single contact grouping

Shell Material:

Aluminum alloy

Included Contact Quantity:

8 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round keyed

Included Contact Type:

Banana single mating end single contact grouping

Thread Series Designator:

Uns and uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0