

View Online at <https://aerobasegroup.com/nsn/5935-00-258-4117>

**Thread Class:**

2a

**Thread Pitch Diameters:**

+2.250/+2.893 inches

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Height:**

2.312 inches

**Overall Width:**

2.312 inches

**Unthreaded Mounting Hole Diameter:**

0.169 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.944 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.944 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

lk-a34 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

30.0 single mating end 1st contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

2940.0 single mating end 1st contact grouping

**Polarization Method:**

Mating end

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

6

**Thread Size:**

2.250 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Silver single mating end single contact grouping

**Insert Material:**

Plastic phenolic single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Chromate

**Included Contact Quantity:**

4 single mating end 1st contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.034 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Acme

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0