NSN 5935-00-258-4117

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-258-4117 **Thread Class:** 2a **Thread Pitch Diameters:** +2.250/+2.893 inches **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Height:** 2.312 inches **Overall Width: 2.312 inches Unthreaded Mounting Hole Diameter:** 0.169 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.944 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.944 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** lk-a34 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 30.0 single mating end 1st contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 2940.0 single mating end 1st contact grouping **Polarization Method:** Mating end **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi):

Thread Size:

2.250 inches

NSN 5935-00-258-4117

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Plastic phenolic single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Chromate
Included Contact Quantity:
4 single mating end 1st contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.034 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0