## NSN 5935-00-258-4665

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-258-4665 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Wall type **Overall Height:** 1.250 inches **Overall Width:** 1.656 inches **Body Length:** 2.531 inches **Environmental Protection:** Salt water resistant **Distance Between Mounting Facility Centers:** 3.281 inches **Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Position Arrangement Style:** "2, 2-20" single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 15.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 125.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 125.0 single mating end single contact grouping **Polarization Method:** Contact **Connector Locking Method:** Spring friction **Connector Cable Strain Relief Method: Bracket** Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches

Terminal Location:

Terminal Education:

Back single mating end single contact grouping

## NSN 5935-00-258-4665

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Insert Material:
Plastic phenolic single mating end
Terminal Type:
Screw single mating end single contact grouping
Included Contact Quantity:
2 single mating end single contact grouping
Included Contact Type:
Flat socket single mating end single contact grouping
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A039b0