NSN 5935-00-258-5845

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-258-5845

Overall Height: 2.562 inches Overall Width: 1.125 inches Body Length: 3.562 inches Cable Entrance Diameter: 0.750 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping		
Overall Width: 1.125 inches Body Length: 3.562 inches Cable Entrance Diameter: 0.750 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping		
1.125 inches Body Length: 3.562 inches Cable Entrance Diameter: 0.750 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping		
Body Length: 3.562 inches Cable Entrance Diameter: 0.750 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping		
3.562 inches Cable Entrance Diameter: 0.750 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping		
Cable Entrance Diameter: 0.750 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping		
0.750 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping		
Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping		
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping		
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping		
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping		
Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping		
10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping		
Contact Maximum Ac Voltage Rating In Volts: 730.0 single mating end single contact grouping		
730.0 single mating end single contact grouping		
Contact Maximum Dc Voltage Rating In Volts:		
730.0 single mating end single contact grouping		
Polarization Method:		
Fixed contact to contact		
Shell Type:		
Hood, top opening		
Connector Cable Strain Relief Method:		
Cable clamp		
Terminal Location:		
Back single mating end single contact grouping		
Contact Material:		
Copper alloy single mating end single contact grouping		
Contact Surface Treatment:		
Cadmium single mating end single contact grouping		
Insert Material:		
Plastic polyester single mating end		
Terminal Type:		
Tab, solder lug single mating end single contact grouping		
Shell Material:		
Steel		
Shell Surface Treatment:		
Paint		
Included Contact Quantity:		
33 single mating end single contact grouping		

Included Contact Type:

Flat pin single mating end single contact grouping

NSN 5935-00-258-5845

Electrical Plug Connector - Page 2 of 2



Special	Features:
---------	-----------

Polarizing contact no14

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0