NSN 5935-00-258-6267

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-258-6267 **Body Style:** Flange mount **Overall Length:** 1.906 inches **Bushing Diameter:** 2.187 inches **Mounting Hole Circle Radius:** 1.359 inches **Overall Diameter:** 3.125 inches **Unthreaded Mounting Hole Diameter:** 0.203 inches **Distance From Mounting Shoulder To Rear Face:** 1.812 inches **Mating End Quantity: Contact Position Arrangement Style:** 4 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 20.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Polarization Method:** Contact Shell Type: Armored **Connector Locking Method:** Contact twistlock **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Plastic phenolic single mating end **Terminal Type:** Screw w/wire lock single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** Nickel

NSN 5935-00-258-6267

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-14, type cfg military specification single material response single mating end

Included Contact Quantity:

3 single mating end 2nd contact grouping

Included Contact Type:

Curved socket w/outside lip single mating end 1st contact grouping

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.