## NSN 5935-00-258-6368

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-258-6368

**Body Style:** 

Straight shape, internal coupling w/strain relief

**Body Length:** 

1.172 inches

**Overall Diameter:** 

1.141 inches

**Environmental Protection:** 

Moisture resistant and vibration resistant and salt water resistant

**Cable Entrance Diameter:** 

Between 0.350 inches and 0.385 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

14-37 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

400.0 single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet latch

**Connector Cable Strain Relief Method:** 

Cable clamp

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:** 

Plastic epoxy single mating end and glass single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, class 1, type 2 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:** 

Solder well single mating end single contact grouping

## **NSN 5935-00-258-6368**Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and nickel
Shell Surface Treatment Specification:
Qq-p-416, type 2 federal standard 1st treatment response and qq-n-290 federal standard 2nd treatment response
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surface gold and contact surface silver
Precious Material And Weight:
0.037 gold grains, troy and 0.037 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.