NSN 5935-00-258-9896

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-258-9896 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Red **Body Style:** Threaded bushing mounted **Overall Length:** 0.672 inches **Mounting Bushing Length:** 0.204 inches **Body Length:** 0.438 inches **Overall Diameter:** 0.438 inches **Bushing Accommodation Hole Shape:** Round **Maximum Voltage Rating In Volts:** 750.0 ac **Accommodated Finger Type:** Banana spring single finger **Finger Accommodation Diameter:** 0.163 inches single finger **Finger Accommodation Length:** 0.234 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.310 inches **Capacitance In Picofarads: Current Rating In Amps:** 15.0 **Mounting Facility Type And Quantity:** 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:**

0.250 inches **Terminal Type:**

Tab, solder lug

NSN 5935-00-258-9896

Tip Jack - Page 2 of 2



Material:
Plastic insulator
Material:
Plastic insulator
Surface Treatment:
Nickel spring
Surface Treatment:
Nickel spring
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig: A03400