## NSN 5935-00-258-9913

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-258-9913 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 2.313 inches **Overall Height:** 2.000 inches **Overall Width:** 2.000 inches **Environmental Protection:** Moisture resistant and vibration resistant and salt water resistant **Unthreaded Mounting Hole Diameter:** 0.147 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.563 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.563 inches **Distance From Mounting Shoulder To Front Face:** 0.672 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 28-21 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 110.0

Shell Type:

Solid

## NSN 5935-00-258-9913

Electrical Receptacle Connector - Page 2 of 2



| Connector Locking Method:  |
|--|
| Externally threaded shell  |
| Thread Length:   |
| 0.625 inches and 0.375 inches  |
| Thready Qty Per Inch (tpi):  |
| 18 and 18  |
| Thread Size:   |
| 1.438 inches and 1.750 inches  |
| Terminal Location:   |
| Back single mating end single contact grouping                         |
| Contact Surface Treatment:   |
| Gold single mating end single contact grouping                         |
| Terminal Type:   |
| Solder well single mating end single contact grouping                  |
| Shell Surface Treatment:   |
| Cadmium  |
| Shell Surface Treatment Specification:                                 |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |
| Included Contact Quantity:   |
| 37 single mating end single contact grouping                           |
| Included Contact Type:   |
| Round pin single mating end single contact grouping                    |
| Precious Material And Location:  |
| Contact surface gold   |
| Precious Material:   |
| Gold   |
| Thread Series Designator:  |
| Unef and unef  |
| Specification Or Standard:   |
| Ms3100c28-21px part  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A039b0   |
|  |