NSN 5935-00-258-9977

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-258-9977 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 2.000 inches **Overall Height:** 0.844 inches **Overall Width:** 0.750 inches **Environmental Protection:** Humidity resistant **Distance Between Mounting Facility Centers:** Between 1.682 inches and 1.692 inches **Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 34 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1800.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Screw **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping or gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

NSN 5935-00-258-9977

Electrical Receptacle Connector - Page 2 of 2



Terminal	Type:
----------	-------

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-19833, type gdi-30 military specification single material response single mating end

Included Contact Quantity:

34 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver and contact surfaces gold

Precious Material And Weight:

0.034 silver grains, troy and 0.034 gold grains, troy

Precious Material:

Silver and gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.