

View Online at <https://aerobasegroup.com/nsn/5935-00-259-0103>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, internal coupling

Overall Diameter:

Between 0.672 inches and 0.703 inches

Environmental Protection:

Pressure proof

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

2

Contact Removability:

Nonremovable all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Thread Qty Per Inch (tpi):

32 and 32

Thread Size:

0.375 inches and 0.375 inches

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Silver all mating ends all contact groupings

Insert Material:

Plastic all mating ends

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 2nd mating end all contact groupings

Included Contact Type:

Coaxial socket all mating ends all contact groupings

Precious Material And Location:

Contact and shell surfaces silver

Precious Material And Weight:

0.110 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0