NSN 5935-00-259-0330

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-259-0330

Body Style:
Chassis type
Overall Length:
2.250 inches
Overall Height:
1.156 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Distance Between Mounting Facility Centers:
1.906 inches
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
15.0 single mating end 2nd contact grouping
Contact Maximum Ac Voltage Rating In Volts:
25.0 single mating end 1st contact grouping
Polarization Method:
Contact
Shell Type:
Solid
Connector Locking Method:
Contact twistlock
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end 2nd contact grouping
Insert Material:
Plastic phenolic single mating end
Plastic phenolic single mating end Terminal Type:
Terminal Type:
Terminal Type: Screw single mating end all contact groupings
Terminal Type: Screw single mating end all contact groupings Shell Material:
Terminal Type: Screw single mating end all contact groupings Shell Material: Copper alloy
Terminal Type: Screw single mating end all contact groupings Shell Material: Copper alloy Shell Surface Treatment:
Terminal Type: Screw single mating end all contact groupings Shell Material: Copper alloy Shell Surface Treatment: Nickel
Terminal Type: Screw single mating end all contact groupings Shell Material: Copper alloy Shell Surface Treatment: Nickel Insert Material Specification:

NSN 5935-00-259-0330

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location: Contact and terminal surfaces gold Precious Material And Weight: 0.002 gold grains, troy Precious Material: Gold Shelf Life: N/a Unit Of Measure: -Demilitarization: No Fiig: A039b0

Mil-std (military Standard):

Mil-m-14 spec.