

View Online at <https://aerobasegroup.com/nsn/5935-00-259-0403>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.793 inches

Overall Height:

0.363 inches

Overall Width:

0.414 inches

Environmental Protection:

Weatherproof

Cable Entrance Diameter:

Between 0.122 inches and 0.126 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Removable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Compression nut

Thready Qty Per Inch (tpi):

32 and 32

Thread Size:

0.250 inches and 0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact and body surfaces silver

Precious Material And Weight:

0.105 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unef and unef

Specification Data:

96906-ms35123 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0