Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-259-0634

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.938 inches
Overall Height:
2.250 inches
Overall Width:
2.250 inches
Unthreaded Mounting Hole Diameter:
0.173 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width
1.750 inches
Distance From Mounting Shoulder To Front Face:
0.875 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
32-1 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
41.0 single mating end 1st contact grouping
Contact Maximum Ac Voltage Rating In Volts:
900.0 single mating end 3rd contact grouping
Contact Maximum Dc Voltage Rating In Volts:
1750.0 single mating end 1st contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell

Width:

Electrical Receptacle Connector - Page 2 of 2



Thready Qty Per Inch (tpi):

18

## **Thread Size:**

2.000 inches

# **Terminal Location:**

Back single mating end single contact grouping

## **Terminal Type:**

Solder well single mating end single contact grouping

#### Shell Material:

Aluminum alloy

## **Included Contact Quantity:**

2 single mating end 3rd contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

#### **Test Data Document:**

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

Uns

Specification Data:

81349-mil-c-5015 government specification

## Shelf Life:

N/a

#### Unit Of Measure:

--

#### **Demilitarization:**

No

Fiig:

A039b0