## NSN 5935-00-259-2566

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-259-2566 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Black **Body Style:** Threaded bushing mounted **Overall Length:** 1.030 inches **Mounting Bushing Length:** 0.380 inches **Body Length:** 0.570 inches **Overall Diameter:** 0.380 inches **Bushing Accommodation Hole Shape:** Round **Maximum Voltage Rating In Volts:** 11000.0 dc **Accommodated Finger Type:** Test prod single finger **Finger Accommodation Diameter:** 0.081 inches single finger **Finger Accommodation Length:** 0.500 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.250 inches **Capacitance In Picofarads: Thread Length:** 0.380 inches **Current Rating In Amps: Mounting Facility Type And Quantity:** 1 bushing Thready Qty Per Inch (tpi): 32

Thread Size: 0.250 inches

## NSN 5935-00-259-2566

Tip Jack - Page 2 of 2



Terminal Type:
Tab, solder lug
Material:
Plastic, polyamide cap
Material:
Plastic polyamide cap
Precious Material And Location:
Contact and terminal surfaces silve
Precious Material:
Silver
Surface Treatment:
Silver contact
Surface Treatment:
Silver terminal
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A03400