
NSN 5935-00-259-2566

Tip Jack - Page 1 of 2

Thread Class:





2a **Thread Direction: Right-hand Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Black **Body Style:** Threaded bushing mounted **Overall Length:** 1.030 inches Mounting Bushing Length: 0.380 inches **Body Length:** 0.570 inches **Overall Diameter:** 0.380 inches **Bushing Accommodation Hole Shape:** Round Maximum Voltage Rating In Volts: 11000.0 dc Accommodated Finger Type: Test prod single finger **Finger Accommodation Diameter:** 0.081 inches single finger Finger Accommodation Length: 0.500 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.250 inches Capacitance In Picofarads: 2.0 **Thread Length:** 0.380 inches **Current Rating In Amps:** 10.0 Mounting Facility Type And Quantity: 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.250 inches

NSN 5935-00-259-2566

Tip Jack - Page 2 of 2



Terminal Type:
Tab, solder lug
Material:
Plastic, polyamide cap
Material:
Plastic polyamide cap
Precious Material And Location:
Contact and terminal surfaces silver
Precious Material:
Silver
Surface Treatment:
Silver contact
Surface Treatment:
Silver terminal
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A03400