Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-259-3256

Thread Class:
2a
Za Thread Direction:
Right-hand
Body Style:
Thru-hole mount w/lockin
Overall Length:
1.015 inches
Bushing Diameter:
0.875 inches
Overall Diameter:
1.031 inches
Environmental Protection:
Moisture resistant and vibration resistant and pressure proof
Unthreaded Mounting Hole Diameter:
Between 0.207 inches and 0.213 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.933 inches and 1.943 inches
Distance From Mounting Shoulder To Front Face:
Between 0.875 inches and 0.891 inches
Distance From Mounting Shoulder To Rear Face:
0.656 inches
Mounting Facility Thickness:
0.359 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
36-8 single mating end
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
23.0 single mating end 1st contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end all contact groupings
Polarization Method:
Contact
Thread Length:
0.625 inches

Electrical Receptacle Connector - Page 2 of 2



Thready Qty Per Inch (tpi):

16

## Thread Size:

2.250 inches

# **Terminal Location:**

Back single mating end all contact groupings

## **Contact Material:**

Copper alloy single mating end all contact groupings

## **Contact Surface Treatment:**

Silver single mating end all contact groupings

#### **Insert Material:**

Rubber single mating end

# **Terminal Type:**

Solder well single mating end all contact groupings

#### Shell Material:

Aluminum alloy

## **Included Contact Quantity:**

46 single mating end 2nd contact grouping

# **Bushing Accommodation Hole Shape:**

Round

Included Contact Type:

Round pin single mating end all contact groupings

# Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A039b0