
NSN 5935-00-259-3306

Tip Jack - Page 1 of 2





Thread Class: 2a **Thread Direction: Right-hand Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Black **Body Style:** Threaded bushing mounted **Overall Length:** 0.922 inches Mounting Bushing Length: 0.500 inches **Body Length:** 0.641 inches **Overall Diameter:** 0.406 inches **Bushing Accommodation Hole Shape:** Round Maximum Voltage Rating In Volts: 1000.0 ac Accommodated Finger Type: Test prod single finger **Finger Accommodation Diameter:** 0.080 inches single finger Finger Accommodation Length: 0.641 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.250 inches **Current Rating In Amps:** 5.0 Mounting Facility Type And Quantity: 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.250 inches **Terminal Type:** Turret Material: Plastic, polyamide insulator

NSN 5935-00-259-3306

Tip Jack - Page 2 of 2

Plastic polyamide insulator Precious Material And Location: Contact spring surface silver Precious Material: Silver Surface Treatment: Tin terminal Surface Treatment: Tin terminal

Thread Series Designator:

Unef

Material:

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03400

