NSN 5935-00-259-3330

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-259-3330 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, latching **Overall Length:** 0.531 inches **Bushing Diameter:** 0.500 inches **Overall Width:** 0.766 inches Diameter: 0.562 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Mh-5 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Contact **Connector Locking Method:** Latching ring Thread Length: 0.250 inches Thready Qty Per Inch (tpi): **Thread Size:** 0.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping

Gold single mating end single contact

Insert Material:

Plastic melamine single mating end

NSN 5935-00-259-3330

Mil-std (military Standard):

Mil-m-14 spec.

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Insert Material Specification:
Mil-m-14, type mme military specification single material response single mating end
Included Contact Quantity:
5 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0